Leading Innovation, Creating Tomorrow





## **Automation Solution**










Powerful HMI Software Armed with Advanced Graphics Technology




The Pinnacle of HMI Software, XGT InfoU Meet the Innovative Technology of LSIS!





# Installing infoU speed up the work-process time.

InfoU dramatically expedites development by automation of time-consuming tasks like tag entry and database connection. Its communication simulator lets you test applications under true-to-life conditions even without actual equipment, while its cross-reference capability promptly identifies and corrects alarm/logging settings containing incorrect mapping information.





XGT InfoU offers complete satisfaction by combining breakthrough technology with a comfortable work environment.

Today, HMI products are becoming increasingly sophisticated and diversified to facilitate the creation of flexible production systems.


As a result, system developers devote long hours to HMI-related tasks, and the ensuing rise in cost remains a difficult challenge for developers to solve.

In addition, to enable real-time operation through connectivity with upper system like MES, an integrated software environment for floor control is absolutely essential.

InfoU guarantees a stable work environment that lets developers analyze the problems they face and achieve their desired goals with

# Breakthrough Technology Meets Exceptional, Convenient Performance.

- Integrated development environment featuring an intuitive user interface and cutting-edge graphics technology.
- Template function enabling diverse, convenient data collection for integration with other LSIS products like XGT PLC.
- Efficient problem solving using enhanced alarm features.
- Open architecture that supports leading industrial standards including OPC and OLE/DB.
- Powerful scripting language including schedule management.
- Easy to use for anyone.
- Program development environment allowing easy application.



## **Tag Simulator**

Drastically reduces debugging time by letting users run applications under true-to-life conditions even without actual devices, by supplying tag data using random sin-cos functions.

#### **Cross Reference**

Offers shortcut support that locates selected files and objects from screens, alerts, alarms, and logging data, thus dramatically reducing work time by allowing users to quickly find items even when tag properties have been modified or deleted.


#### **Templates**

Can be run using common variables with XGT PLC, and significantly reduces cost by offering an auto-generation function for drawings.

# Integrated Development Environment Featuring an Intuitive UI and Cutting-Edge Graphics Technology

#### Drawing Support with Diverse Objects and a Graphics Library

- **⊇** InfoU comes equipped with a graphics library and a wide selection of objects to let users create unique drawings.
- InfoU supports all major graphic file formats, including BMP, GIF, JPEG, PNG, TIFF, ICON, WMF, and EMF.
- The animation GIFs feature lets you enjoy animation effects according to different bit conditions.
- InfoU lets you insert ActiveX Controls directly into drawings and control them using a variety of methods, including embedded scripts.



## **VBS Support for Flexible Application**

- **∃** InfoU offers VB script for powerful and flexible applications.
- **될** It includes Visual Basic Lanaguge / Action Trigger editing functions.


## Fast Screen Configuration Using a Convenient GUI

InfoU helps engineers configure systems easily by providing an intuitive menu hierarchy and a structured development environment. Its graphical user interface (GUI) has an intuitive menu and object-oriented O/S that let engineers configure screens quickly and conveniently.



#### Extensive Symbol Library for Variegated Use of Objects


- InfoU comes with a symbol library containing over 1,000 items.
- Drag-and-drop makes using the library fast and easy.





#### **Animation Attribute Editing and Diverse Tag Settings**

- Dynamic Characteristics
  - Visible/invisible, blinking, horizontal size, vertical size, horizontal move, horizontal fill, vertical fill, color, background color, font color, rotation, value display.
- User Actions
  - Horizontal drag, vertical drag, value entry(text, digital value, analog value), touch action (designation of pre-defined action).
- → Virtual keyboard for panel PCs.




#### Dedicated Screens for Equipments and Devices to Ensure Stable Expandability

- InfoU provides dedicated screens for ActiveX Controls used in plant screen editing and monitoring.
  - Alarms and events view (real time/history).
  - Trend (real time/history)
  - GIMAC, GIPAM vector graphics and common ActiveX Controls.



#### Fast, Accurate Process Management with Panning and Navigation

→ Full screen viewing with close up of specific work areas.



#### Work Made Quick and Easy with a Convenient Tag Selection Window

- Tag names can be entered directly in the dialog box for setting dynamic characteristics, or selected using the tag selection window.
- Mathematical and logical expressions supported.


# **Layer Function for Convenient work**


∋ Show/hide selected layer, layer lock, activate current layer.



#### **Effortless UI with Graphic Runtime Environment Settings**

■ A preview function lets you check in advance how the screen will appear when executing runtime.






# **Progressive Project Management through Tag Integration**

#### Tag Integration with LSIS PLC

- InfoU can be integrated with various LSIS products through Variable sharing when using XGT/GLOFA PLC.
- **⊇** The points used in XG5000 or GMWIN can be directly entered as tags in InfoU using the tag import function.




### **Engineering Tasks Made Easy with Tag Import and Entry**

- ⊇ Input/output devices and stations configured simultaneously in the tag database without the use of separate screens.
- 2 Auto tag generation supported for LSIS devices and equipment, including PLC.
- Compatible with tag databases and Microsoft Excel.
- → One-click setting for all tag properties.
- ≥ New tags added simply by renaming when saving similar tags.
- ➡ Changed tag properties represented in bold type, errors represented in red.
- Explanation for each tag property displayed at the bottom of the tag property box.
- □ Checks for error when changing tag properties as well as when saving
- Save changed tag property notification when moving to the next tag after changing a tag property.
- ≥ Multi-item selection enabled for easy deletion of large numbers of items.
- → Tag property searching by group or alphabetical order.
- 2 In the index, tag names clearly differentiated from other properties by bold type.
- ≥ Important items emphasized with yellow background and blue font color.
- Supports "Freeze Panes" function similar to Microsoft Excel.
- Supports "Auto Search" for easy searching by directly entering terms without using a separate search screen.

# Resource Reuse for Building User Libraries


- ⇒ An item that has been used once can be saved in the library manager and reused by the registered user.
- Objects, including scripts and properties, can be added.






# **Automatic Tag Generation for LSIS Devices**

- When using LSIS devices and equipment, tags are generated automatically during drive creation, thus eliminating the need to enter them separately.
- 2 Communication-related status tags are generated automatically during drive registration, for easy network monitoring.




# Fast Editing with Excel Import & Export Support

■ Supports tag database import/export with Microsoft Excel for easy largescale editing of tags.



## **Custom Objects for Devices**


■ Template objects are provided for frequently used devices, to enable immediate use.



# Varied and Convenient Data Collection Models


#### **Enhanced Efficiency through Varied Data Collection Models**


- InfoU supports diverse data collection models, including fixed-cycle, statistical (average, maximum, minimum), and integrated, which can be used in trends and reports.
- ➡ Fixed-cycle: Tag values are collected at regular intervals.
- 3 Statistical value: Statistical data for selected tags are generated at regular intervals.
- Integrated value : Statistical data on integrated values are generated for tags whose values accumulate.
- **The second of the second of t**
- 2 Selective saving: When user-designated conditions are met, registered tag values are collected over a set duration. Allows the tracking of tag changes before and after.



#### **Enhanced Efficiency through Automatic Generation of Statistical Data**

- infoU can generate statistical data without relying on separate scripts and external applications.
- 2 Complicated reports can be compiled simply using the provided statistical data.
- The statistical data can be checked promptly during runtime through trend objects, etc.
- **I** In the case of digital tags, status information including maintained time and activation count can be collected automatically.







# **Automatic Backup**

- All collection models can be stored separately through the automatic backup function.
- 3 Saved backup files can be stored permanently as DAT using a CD writer.
- 3 Backed-up collection data may be restored and used as needed.


# Collection Data Visualization Using a Web Browser


- ⊇ Collected data can be used by external users through the InfoU Web server.
- 2 With the InfoU Web server, users can access collected data directly through Trend, without using separate operations.



# **Management of Collected Data**

- InfoU provides Trend for analyzing collected data.
- ⊇ InfoU Trend has a wide range of functions to accommodate the user's various needs.
- Trend data can be saved directly as a Microsoft Excel file.
- ⇒ API allows data collected from external applications to be utilized in InfoU.
- Collected data can be used directly in reports.





# **Efficient Problem Solving Using Enhanced Alarm Features**


#### Provision of Variegated Information for Maximum Management Efficiency

- >>> When an alarm occurs, it triggers such actions as alarm sounds, printing, SMS transmission, and email transmission.
- → The settings for such actions can be configured by alarm group.
- 2 Once a tag is registered in an alarm group and an alarm occurs for the tag in question, the tasks designated in the group settings are executed.
  - Settings by alarm group: Tags are registered by group and the same tasks are executed for the tags in the entire group.
  - Alarm level by group: If the alarm level has not been set individually for a
    particular tag, it may be set collectively by group.
  - Alarm sounds: When an alarm occurs, the wave file designated for the relevant group is played.
  - Alarm printing: When an alarm occurs, the printer registered for the relevant group prints out the alarm information. A specific color may be set by alarm level and type.
  - SMS transmission: Alarm may be received remotely by messages sent to the registered user's mobile phone.
  - Email transmission: Alarm status messages are transmitted via email




#### Easy Operation Using Alert Sound/Auto Print Settings

- ≥ Each alarm group can be customized with its own alarm sound and print settings.
- Setting alarm properties by group allows users to form an entire alarm system with ease.



#### Instantaneous System Error Recognition that Minimizes Damage

- Prompt identification of system errors helps minimize down time. InfoU supports a wide range of alarm types, and swiftly provides necessary information using various analytical tools and filters.
  - Response by alarm type: All alarm, whether real-time or history-related, are classified into three categories—process alarm, system alarms, and event alarm—and handled accordingly.
  - Process alarm: Handles alarm for registered tags, according to the designated alarm level (1 to 10).
  - System alarm: Reports system errors that users need to be aware of in order to operate the system.
  - Event alarm : Collects and saves information needed by the user, including control input content, user log-in information, script execution status, etc.
- A variety of analog alarm types (boundary values, modified time, etc.) can be set for close observation of process conditions.
- Alarm properties may be controlled directly from the drawings screen.



#### **Instant Access to Drawings through Cross Reference**


- The cross reference function takes users directly to the drawing for which an alarm has occurred.
- 3 Users can immediately check the equipment that has triggered the alarm.





### **SMS/Email Settings**

2 Configuring SMS/email activation settings and registering prospective recipients allow prompt and automatic transmission of information in case of alarm.



## **Convenient Alarm Group Management**

- 3 Managing alarms by group lets users keep control of their projects with ease.
- ≥ Tag selection can be made for multiple items at a time or registered by group.




# Flexible Alarms for Improved Efficiency

- Registered bit tags can be used to directly and indirectly activate or inactivate alarm activation.
- ≥ By setting alarm priority, information display can be prevented for a particular alarm. Priority settings can be applied by level, tag, or group.
- Alarms can be managed as a group according to location and user, with easy access during configuring drawings.


#### Alarm Message Settings for Quick Error Identification

- Users can set the alarm message that will be displayed when an error occurs or is restored.
- ≥ Alarm messages can be set as occurrence, recovery, common, or user-defined. When saving similar alarm messages, new messages may be added simply by renaming.
- ➡ Errors can be verified when changing properties as well as when saving, to prevent user mistakes.
- **→** Multi-item selection makes it easy to delete a large number of items at once.
- Supports the Freeze Panes function, similar to Microsoft Excel. With Auto Search, searches can be performed by directly entering the search terms without pulling up a separate search screen.



### Guaranteed System Expandability with Alarm API


➡ Third parties, SI(System Integrator) provider, and end-users can use the alarm API (application programming interface) to expand the InfoU system by recording the relevant devices, providers for user alarms, and alarmrequesting individuals.



# Open architecture that supports leading industrial standards including OPC and OLE DB


## **Effortless Construction of Database Applications**

- Supports data exchange between InfoU and external databases connected using OLE DB.
- The various tasks for data exporting can be performed via the scheduler or scripts.
- External data can be gueried and set as InfoU tag data.
- InfoU tag data can be written, renewed, and deleted through external databases.




#### Perfect Compatibility with Other Systems Using a Standard Interface

- InfoU comes equipped with the OPC DA Server/Client. By using a standard interface, the InfoU OPC Server lets users acquire data from LSIS systems through the OPC Client even when using a control system manufactured by another company.
- 2 Because tags can be shared selectively as necessary, important tags can be protected from exposure to external applications.



# Easy Connectivity with Common Types of DBMS


With the data export function, InfoU can be applied easily using internal functions even when the user is not familiar with common database programs like Microsoft SQL Oracle. In addition, a dedicated API is provided for advanced users, so that they can build DB applications using program tools like VB and VC.






# **Stable and Effective Client/Server Architecture**


■ The most widely-used system setting for automation applications is the client/server architecture. In such an architecture, software is installed on the server and accessed by client computers. This saves the time and cost required for software maintenance and repair, while providing additional security and redundancy.



## **Resolution Independent Graphics**

Developing an application at one screen resolution and running it at another resolution will not affect the original application. Applications can be run at a user-defined resolution instead of the screen resolution, so that the advantages of different monitors can be utilized within a single application regardless of where the window is opened. Using Dynamic Resolution Conversion saves time by eliminating the need to re-design, copy, or modify the original application. It also lets you run applications anywhere, regardless of screen size.






# Powerful Scripting Language Including Schedule Management


# **A Scripter Offering Diverse Functions**

- InfoU's scripter is based on VB. Scripts can not only be used to control tag
  values and status, but they also allow access and control the status of graphic
  objects and all alarms.
- The editor provided with InfoU helps users program scripts easily, while the hundreds of included functions amply reflect the demanding needs of users.
  - Supports VB scripts.
  - Allows insertion of COM, OLE Objects.
  - Supports text colors and dot operation for VB styles.
  - Compile error check function included.



## **VBS** Use in the Graphics Editor

- TVBS can be used in the graphics editor to control objects while executing runtime.
- 2 VBS can be applied to events such as dynamic characteristics alteration and mouse movement.



## Trigger Function that Lets Users Select a Variety of Actions


- Scheduled and periodic actions can be selected.
- → Tag data changes can be selected.
- Tag alarm statuses can be selected.

#### **Support for Variegated Functions**

- ⇒ A wide variety of functions are provided for controlling InfoU using the VB scripter.
- Using VB, external applications including third-party ActiveX Controls and Microsoft Excel can be run using COM Ole objects.
- User alarms can be generated using VB.

## **Diverse Options for Schedule Management**

- → Holidays can be set and managed.
- Schedules can be set up by day, week, month, or year.
- Specific dates can be selected.



## **VB Script Debugging**


- Debugs errors in written scripts.
- The VB compile error check function checks for errors as you edit, preventing user mistakes.
- 2 Users can check scripts in advance by using the preview function in the plan and schematics editor.



# Easy to Use for Anyone


#### **Input/Ouput Driver**

- Automatic block generation
  - Even when the user does not set an address block, one is generated automatically through the tag's I/O address while executing runtime.
- Automatic addition of station-related system Tags
  - When adding a new station, related system tags are registered automatically. Station status and communication performance can be checked using the auto-registered system tag values.




# **Easy Error Correction through Cross Reference**

■ When altering or deleting tags, those used in plans and schematics need not be located and deleted individually, but corrected instantly using the cross reference function. Cross reference also lets you quickly locate and correct faulty configurations even after the relevant tags have been deleted.




#### **Effortless Crossover with External Devices Using Excel**

▶ With LSIS PLCs, such as XGT, tags can be shared with the XG5000 program tool, thus eliminating the need for separate tag entry. But with devices made by other companies, updating and adding tags can be a time-consuming endeavor. In such cases, using worksheet programs like Microsoft Excel can make the entire process fast and simple.




# **Tag Simulator**

- 2 Operation tests can be run using the tag simulator even in the absence of actual equipment.
- Screens are displayed conveniently using various sources, including triangle and saw-tooth waves.



# InfoU Web Server







# **Easy Report Generation Using the Report Wizard**

### A Wizard that Lets Both Developers and Operators Create Forms with Ease

- 2 Reports come in the form of a Wizard, so that operators as well as developers can register forms directly without the need for separate base technologies.
- 2 Once the collection model is selected, the corresponding tag list is displayed. The type of data that can be selected is determined by the property of the collection model.
  - Fixed-cycle: Analog current value, digital current status.
  - Statistical value (analog): Current value, minimum value, maximum value, minimum time, maximum time, average, total, sampling count.
  - Statistical value (digital): On count, activation time, alteration count.
- 🔁 Daily, weekly, and monthly reports can be printed and saved automatically. When saving, users can specify how long the saved file will be kept.
- Report forms can be selected and printed by users whenever necessary.



# **Ordering information**



Item	Product	Description
Developer and Runtime version	InfoU-RC-75	78 tags
	InfoU-RC-150	150 tags
	InfoU-RC-500	500 tags
	InfoU-RC-1K	1,000 tags
	InfoU-RC-2K	2,000 tags
	InfoU-RC-MAX	Unlimited tags
Runtime Version	InfoU-RT-75	78 tags
	InfoU-RT-150	150 tags
	InfoU-RT-500	500 tags
	InfoU-RT-1K	1,000 tags
	InfoU-RT-2K	2,000 tags
	InfoU-RT-MAX	Unlimited tags
Web Version	InfoU-OP-WEB2	InfoU-RC-MAX + Web server (Access limit: Max. 2person)
	InfoU-OP-WEB5	InfoU-RC-MAX + Web server(Access limit: Max. 5person)
	InfoU-0P-WEB10	InfoU-RC-MAX + Web server(Access limit: Max. 10person)
	InfoU-OP-WEBMAX	InfoU-RC-MAX + Web server (Unlimited access)

Leading Innovation, Creating Tomorrow



- · For your safety, please read user's manual thoroughly before operating
- Contact the nearest authorized service facility for examination, repair, or adjustment.
- Please contact qualified service technician when you need maintenance Do not disassemble or repair by yourself!
- Any maintenance and inspection shall be performed by the personnel having expertise concerned.

© 2009.9 LS Industrial Systems Co., Ltd. All Rights Reserved.

# LS Industrial Systems Co., Ltd.

#### **■ HEAD OFFICE**

LS Tower 1026-6, Hogye-dong, Dongan-gu, Anyang-si, Gyeonggi-do 431-848, Korea

 Europe + 82-2-2034-4376 ywsohn@lsis.biz Middle East + 82-2-2034-4901 bonseongk@lsis.biz • South West Asia + 82-2-2034-4645 sunkyup@lsis.biz South East Asia + 82-2-2034-4707 ohpark@lsis.biz · CIS + 82-2-2034-4913 jinhkang@lsis.biz + 82-2-2034-4377 younsupl@lsis.biz America

Specifications in this catalog are subject to change without notice due to continuous product development and improvement.

#### ■Global Network

LS Industrial Systems (Middle East) FZE >> Dubai, U.A.E.

Address: P.O. Box-114216, API World Tower, 303B, Sheikhe Zayed Road, Dubai, U.A.E. Tel: 971-4-332-8289 Fax: 971-4-332-9444 e-mail: hwyim@lsis.biz

• Dalian LS Industrial Systems Co., Ltd. >> Dalian, China

www.lsis.biz

Address: No.15, Liaohexi 3-Road, Economic and Technical Development zone, Dalian 116600, China

Tel: 86-411-8273-7777 Fax: 86-411-8730-7560 e-mail: lixk@lsis.com.cn

•LS Industrial Systems (Wuxi) Co., Ltd >> Wuxi, China
Address: 102-A, National High & New Tech Industrial Development Area, Wuxi, Jiangsu,

214028, P.R. China

Tel: 86-510-8534-6666 Fax: 86-510-522-4078 e-mail: xuhg@lsis.com.cn

•LS-VINA Industrial Systems Co., Ltd >> Hanoi, Vietnam
Address: Nguyen Khe - Dong Anh - HaNoi - VietNam
Tel: 84-4-882-0222 Fax: 84-4-882-0220 e-mail: srjo@hn.vnn.vn

• LS Industrial Systems Tokyo Office >> Tokyo, Japan Address: 16FL, Higashi-Kan, Akasaka Twin Tower 17-22, 2-chome, Akasaka, Minato-ku

Tokyo 107-8470, Japan Tel: 81-3-3582-9128 Fax: 81-3-3582-2667 e-mail: jschuna@lsis.biz

•LS Industrial Systems Shanghai Office >> Shanghai, China
Address: Room E-G, 12FL Huamin Empire Plaza, No.726, West Yan'an Road Shanghai

200050, P.R. China
Tel: 86-21-5237-9977 (609) Fax: 89-21-5237-7191 e-mail: jinhk@lsis.com.cn

•LS Industrial Systems Beijing Office >> Beijing, China Address: B-Tower 17FL. Beijing Global Trade Center B/D. No.36, BeiSanHuanDong-Lu, DongCheng-District, Beijing 100013, P.R. China Tel: 86-10-5825-6025, 7 Fax: 86-10-5825-6026 e-mail: cuixiaorong@lsis.com.cn

e-mail: cuixiaorong@lsis.com.ci
LS Industrial Systems Guangzhou Office >> Guangzhou, China
Address: Room 1403,14FL, New Poly Tower, 2 Zhongshan Liu Road, Guangzhou,
P.R. China

Tel: 86-20-8326-6764 Fax: 86-20-8326-6287 e-mail: linsz@lsis.biz

Industrial Systems Chengdu Office >> Chengdu, China
 Address: 12FL, Guodong Buiding, No.52 Jindun Road Chengdu, 610041, P.R. China
 Tel: 86-28-8612-9151 Fax: 86-28-8612-9236 e-mail: yangcf@lsis.com.cn

 LS Industrial Systems Qingdao Office >> Qingdao, China
 Address: 7B40, Haixin Guangchang Shenye Building B, No.9, Shandong Road Qingdao 26600, P.R. China

Tel: 86-532-8501-6568 Fax: 86-532-583-3793 e-mail: lirj@lsis.com.cn

2009.11 LS XGB (E) 2006.06/(08) 2009. OCT Printed in Korea HumanPower